

DERWENT-ACC-NO: 1992-425577
DERWENT-WEEK: 199746
COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Machine housing type-plate - is transparent with letter and formed in mirror-image on near side, for mounting on machine housing partic portable power tool

INVENTOR: FINKBEINER, T; GRUNDLER, G

PATENT-ASSIGNEE: BOSCH GMBH ROBERT [BOSC]

PRIORITY-DATA:
1991DE-4120504 (June 21, 1991)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
DE 59208842 G	October 9, 1997	N/A	000	G09F 003/00
EP 519337 A1	December 23, 1992	G	007	G09F 003/00
DE 4120504 A1	December 24, 1992	N/A	005	G09F 007/00
EP 519337 B1	September 3, 1997	G	006	G09F 003/00

DESIGNATED-STATES: CH DE GB IT LI CH DE GB IT LI

CITED-DOCUMENTS: 1.Jnl.Ref; BE 905186 ; DE 8803703 ; FR 2632566

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO	APPL-DATE
DE59208842G	N/A	1992DE-0508842	June 12, 1992
DE59208842G	N/A	1992EP-0109885	June 12, 1992
DE59208842G	Based on	EP 519337	N/A
EP 519337A1	N/A	1992EP-0109885	June 12, 1992
DE 4120504A1	N/A	1991DE-4120504	June 21, 1991
EP 519337B1	N/A	1992EP-0109885	June 12, 1992

INT-CL (IPC): G09F003/00; G09F003/02 ; G09F007/00 ; G09F007/16
ABSTRACTED-PUB-NO: EP 519337A

BASIC-ABSTRACT:

Flat type-plate for mounting on a machine housing, partic. portable power tool, has markings giving particulars of the manufacturer and the machine type etc. Plate is of transparent material, with the lettering formed on its rear side furthest from the observer in a mirror-image. This can be done by hot-embossing, etching, laser beam etc. Plate can be of transparent plastic eg. polyester, polycarbonate, PVC or PE. Lettering can alternatively be formed by colour-printing, milling, engraving or rolling.

ADVANTAGE - Easily and permanently legible.

tic

ABSTRACTED-PUB-NO: EP 519337B

EQUIVALENT-ABSTRACTS: Hand tool having an identification plate (1) of platelike

form, which bears a marking (5,6) containing data about the manufacture or type of the hand tool, characterised in that the identification plate (1) consists of transparent plastic, in that the marking (5,6) is made in mirror writing on a reverse side (3), facing away from the observer, of the identification plate (1), in that the identification plate (1) is connected to the hand tool by being slid into a pocket (14) arranged on the hand tool, and in that the pocket (14) comprises a recess in a housing (12) of the hand tool having inwardly protruding edges (15).

CHOSEN-DRAWING: Dwg.1/3 Dwg.1/3

DERWENT-CLASS: A88 P85

CPI-CODES: A11-C04; A12-H; A12-W03;